



شركة الطبيعة لانتاج الاصباغ المحدودة

Al-Tabieaa Paints Producing Co.

Technical Data Sheet

Al-Marjan Acrylic Primer

DESCRIPTION	Al-Marjan Acrylic Primer is high quality acrylic primer based on acrylic polymer having high adhesion, penetrating into cementitious substrates, highly resistant for weathering conditions properties.
RECOMMENDED USE	Al-Marjan Acrylic Primer can be used on all Interior and Exterior concrete and gypsum walls.
TECHNICAL INFORMATION	
Colors	Transparent white.
Finish	Smooth surface finish
Specific Gravity	1.5 ± 0.02
Solid by Weight %	46 ± 2%
Covering Rate	15 m ² /Lit. at 30 micron film
Drying Time at 30 °C	Touch dry : 30 min. Recoatable: 2 hrs. Full cure 24 hrs
SURFACE PREPARATION	
All surfaces to be painted must be clean, dry and sound free of faults, oils, grease, dust and contaminants and should be prepared as per national and international standards for surface preparations like SSPC 13-NACE 6	
APPLICATION DATA	
Application Methods	Brush, Roller or Spray.
Thinning / Cleaning of Tools	Water
Mixing Ratio	5-15%
CONDITIONS DURING APPLICATION	
The temperature of the substrate should be minimum 10°C above the dew point measured in the substrate vicinity.	
MISCELLANEOUS DATA	
STORAGE	Al-Marjan Acrylic Primer should be kept in cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Containers must be kept tightly closed.
HANDLING	Handle with care, mix well before use.
SHELF LIFE	24 months.



شركة الطبيعة لانتاج الاصباغ المحدودة

Al-Tabieaa Paints Producing Co.

SAFETY / HEALTH

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes from skin; use soap and water or a recognized skin cleaner.
- Keep out of reach of children.