



# شركة الطبيعة لانتاج الاصباغ المحدودة

## Al-Tabieaa Paints Producing Co.

### Technical Data Sheet

## Al-Marjan Wall Putty

<b>DESCRIPTION</b>	<b>Al-Marjan Wall Putty</b> is high quality homogeneous polymeric putty, having high adhesion to the substrates and used as ideal filler for uneven masonry surfaces.  Easy to apply easy to sand paste, with very good adhesion, high anti-chalking
<b>RECOMMENDED USE</b>	<b>Al-Marjan Wall Putty</b> can be used on Concrete, Plaster and Woodwork.
<b>TECHNICAL INFORMATION</b>	
<b>Colors</b>	White
<b>Specific Gravity</b>	1.6 ± 0.02
<b>Solid by Weight %</b>	66 ± 2%
<b>Drying Time at 30 °C</b>	Touch dry : 2 hrs. Recoatable: 4 hrs. Full cure 24 hrs
<b>SURFACE PREPARATION</b>	
Surface must be clean, dry and sound free of faults, oils, grease, dust and contaminants and should be prepared as per national and international standards for surface preparations like SSPC 13-NACE 6	
<b>APPLICATION DATA</b>	
<b>Application Methods</b>	Putty knife.
<b>Thinning / Cleaning of Tools</b>	Water
<b>Mixing Ratio</b>	Should be used directly (Not to be thinned)
<b>CONDITIONS DURING APPLICATION</b>	
The temperature of the substrate should be minimum 10°C above the dew point measured in the substrate vicinity.	
<b>MISCELLANEOUS DATA</b>	
<b>STORAGE</b>	<b>Al-Marjan Wall Putty</b> should be kept in cool and well ventilated place, protected from heat and direct sunlight at temp 5-35°C. Bags and containers must be kept tightly closed.
<b>HANDLING</b>	Handle with care, mix well before use.
<b>SHELF LIFE</b>	24 months.
<b>SAFETY / HEALTH</b>	- Ensure good ventilation during application and drying. - Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.